



Aurora® / Gemini™
with Transmitters, Switches, Accessories
Level Application Questionnaire

DATE _____
RFQ# _____

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Customer Information | |
| Company/Contact/Title _____ | |
| E-mail _____ | Phone _____ Fax _____ |
| Design Conditions | |
| Proposed Model Number(s) _____ | |
| Process Media _____ | <input type="checkbox"/> Steam Present <input type="checkbox"/> Suspended Solids Percentage _____ |
| Minimum S.G. _____ | <input type="checkbox"/> Constant <input type="checkbox"/> Changing Range _____ |
| Interface Service _____ | Upper/Lower Liquids S.G.s _____ / _____ Dielectrics _____ / _____ |
| Interface Emulsion Layer <input type="checkbox"/> No <input type="checkbox"/> Yes Thickness _____ | |
| Temperature _____ | Operating _____ Design _____ Ambient _____ |
| Pressure _____ | Operating _____ Design _____ |
| Does liquid boil or flash? <input type="checkbox"/> Yes <input type="checkbox"/> No | |
| Area Classification _____ | <input type="checkbox"/> GP <input type="checkbox"/> Hazardous <input type="checkbox"/> Cl Div _____ Grp _____ <input type="checkbox"/> EP <input type="checkbox"/> NI <input type="checkbox"/> IS |
| Agency Approval Required _____ | <input type="checkbox"/> None <input type="checkbox"/> FM <input type="checkbox"/> CSA <input type="checkbox"/> ATEX <input type="checkbox"/> Other _____ |
| Gauge Specifications | |
| Materials of Construction _____ | Chamber _____ Process Conns _____ Float _____ Internal Coating _____ |
| Process Connections _____ | Size _____ Type _____ Rating _____ |
| If flanges required: Gasket Surface _____ <input type="checkbox"/> Slip-on <input type="checkbox"/> Weldneck <input type="checkbox"/> Other | |
| Process connection centerlines _____ Indication or measurement range _____ | |
| Vent/Drain Conn: 1/2" (F) NPT w/plugs standard If other, please specify _____ | |
| Indicator/Scale _____ | <input type="checkbox"/> Flag <input type="checkbox"/> Shuttle Ruler <input type="checkbox"/> Yes <input type="checkbox"/> No |
| Ruler units of measure: _____ | <input type="checkbox"/> In/Ft <input type="checkbox"/> Running in. <input type="checkbox"/> cm/m <input type="checkbox"/> Percent <input type="checkbox"/> Other _____ |
| Aurora Mounting Configuration _____ | <input type="checkbox"/> Side/side <input type="checkbox"/> Side/bottom <input type="checkbox"/> Other |
| Gemini Mounting Configuration _____ | <input type="checkbox"/> Side/side <input type="checkbox"/> Side/bottom <input type="checkbox"/> Top/side <input type="checkbox"/> Top/bottom <input type="checkbox"/> Other _____ |
| Construction Design Code _____ | <input type="checkbox"/> Standard <input type="checkbox"/> NACE <input type="checkbox"/> ASME B31.3 <input type="checkbox"/> ASME B31.1 <input type="checkbox"/> Other _____ |
| Accessories | |
| Transmitter _____ | <input type="checkbox"/> External reed chain <input type="checkbox"/> Top mount ext magnetostrictive <input type="checkbox"/> Bottom mt ext magnetostrictive |
| Switch(es) _____ | <input type="checkbox"/> Reed, 1 amp SPDT <input type="checkbox"/> Snap, 10 amp DPDT <input type="checkbox"/> Pneumatic |
| Valves _____ | <input type="checkbox"/> Vent <input type="checkbox"/> Drain <input type="checkbox"/> Isolation |
| Type _____ | Material _____ Model _____ |
| Insulation _____ | <input type="checkbox"/> High temp. (up to +500° F (+260° C)) <input type="checkbox"/> Cryogenic |
| | <input type="checkbox"/> High temp. (up to +501° to +1000° F (+261° to +538° C)) |
| Heat Trace _____ | <input type="checkbox"/> Steam <input type="checkbox"/> Electric Supply Voltage _____ Temp to maintain _____ |
| | <input type="checkbox"/> Thermostat |
| Eclipse Guided Wave Radar Specifications | |
| Proposed Model Number(s) _____ | |
| Process Liquid Dielectric _____ | <input type="checkbox"/> Constant <input type="checkbox"/> Changing Range _____ |
| Viscosity _____ | at what temperature _____ |
| Media will coat probe _____ | <input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Film <input type="checkbox"/> Bridging <input type="checkbox"/> Solids |
| Signal Output _____ | <input type="checkbox"/> 4-20 mA <input type="checkbox"/> HART <input type="checkbox"/> Digital display <input type="checkbox"/> Foundation Fieldbus |
| Transmitter enclosure _____ | <input type="checkbox"/> Cast aluminum <input type="checkbox"/> 316 SS <input type="checkbox"/> Integral <input type="checkbox"/> Remote <input type="checkbox"/> 3/4" NPT <input type="checkbox"/> M20 |
| Probe Type _____ | <input type="checkbox"/> Coaxial <input type="checkbox"/> Single <input type="checkbox"/> Twin rod <input type="checkbox"/> Overfill <input type="checkbox"/> HTHP <input type="checkbox"/> HP <input type="checkbox"/> Steam <input type="checkbox"/> Interface |
| O-ring Material _____ | <input type="checkbox"/> Viton GFLT <input type="checkbox"/> EPDM <input type="checkbox"/> Kalrez 4079 <input type="checkbox"/> Aegis PF 128 <input type="checkbox"/> None |
| With respect to the top of the indicator or measuring range: | |
| Max. Level _____ | Normal Level _____ Min. Level _____ |

